

FRAMECAD® Pro-mag™ Magnesium Oxide Board

FRAMECAD® Pro-mag™ Board Complies with

UL 055 and ASTM A rated - Fire resistance (up to 4 hours given correct installation).
 - Waterproof (freeze/thaw tested for 36 months).

ASTM G-21 - Mold and bug free (non-nutrient to mold, fungus and insect life).
 ASTM D-5628 - Impact resistance
 STC Rated 53-54 - Sound
 NYC Approved (MEA #359-02-M)



Metric Dimensions

Application	Thickness (mm)	Width (mm)	Length (mm)				Approximate Loading per 20FTGP
			2400	2700	3000	3600	
Soffit / Ceiling	4.5	1200/1220	●	●	●		1400 Panels
Ceiling / Lining	6	1200/1220	●	●	●		1060 Panels
Lining / Cladding	9	1200/1220	●	●	●		710 panels
	12	1200/1220	●	●	●		530 Panels
Weatherboards (woodgrain)	8	210/310				●	2000 Panels
Flooring	18	1200/1220	●	●	●		355 Sheets

Imperial Dimensions

Application	Thickness (inch)	Width (feet)	Length (feet)				Approximate Loading per 20FTGP
			8'	9'	10'	12'	
Soffit / Ceiling	3/16"	4'	●	●	●		1400 Panels
Ceiling / Lining	1/4"	4'	●	●	●		1060 Panels
Lining / Cladding	3/8"	4'	●	●	●		710 panels
	1/2"	4'	●	●	●		530 Panels
Weatherboards (woodgrain)	3/8"	4'				●	2000 Panels
Flooring	11/16"	4'	●	●	●		355 Sheets

Note: Pro-mag™ magnesium board 6mm (1/4") and 9mm (3/8") available with a tapered edge or square edge.
 Pro-mag™ magnesium board comes in a variety of sizes, if not listed above please contact us with your inquiry.



www.framecad.com